

CLAIM AMENDMENTS

Please cancel claim 1 and amend claims 2 and 4-6. Claims 22-23 were previously withdrawn by the Examiner. No new matter is believed to be introduced by the aforementioned amendments. The following listing of claims will replace all prior versions and listings of claims in the application.

1. **(Cancelled)**

2. **(Currently Amended)** The An optical add/drop patch cord ~~of claim 1,~~ comprising:

an optical add/drop component disposed in a casing, the optical add/drop component comprising:

an optical substrate;

a first thin film formed on a first end of the optical substrate; and

a second thin film formed on a second end that opposes the first end; and

an input fiber permanently coupled to the casing and optically coupled to the optical add/drop component;

a drop fiber permanently coupled to the casing and optically coupled to the optical add/drop component;

an add fiber permanently coupled to the casing and optically coupled to the optical add/drop component; and

an output fiber permanently coupled to the casing and optically coupled to the optical add/drop component;

wherein the first thin film is configured to allow at least one wavelength of an optical signal from the input fiber to pass through the first thin film towards the drop fiber while reflecting other wavelength(s) of the optical signal to the second thin film; and

the second thin film is configured to reflect the other wavelength(s) of the optical signal towards the output fiber while allowing at least one wavelength to pass through the thin film from the add fiber towards the output fiber.

3. **(Original)** The optical add/drop patch cord of claim 2, the optical substrate comprising:

a first cube having a first attachment face; and

a second cube having a second attachment face that is adhered to the first face when pressed together.

4. **(Currently Amended)** The optical add/drop patch cord of claim ~~[[1]]~~ 2, wherein the input, drop, add and output fibers are coupled to the casing using solder ferrules.

5. **(Currently Amended)** The optical add/drop patch cord of claim ~~[[1]]~~ 2, comprising more than four ports configured to add/drop a plurality of signals.

6. **(Currently Amended)** The optical add/drop patch cord of claim ~~[[1]]~~ 2, the optical add/drop component including the collimating elements for ensuring that light is not dispersed within the optical add/drop component.

7. **(Original)** The optical add/drop patch cord of claim 2, the optical substrate including a combination of glass and air.

8. **(Original)** An optical add/drop patch cord comprising:
 an optical add/drop component disposed in a casing, the optical add/drop component comprising:
 an optical substrate;
 a first thin film formed on a first end of the optical substrate; and
 a second thin film formed on a second end such that the second thin film is opposed to the first thin film;
 an input port optically coupled to the optical substrate and arranged to propagate a multiplexed optical signal towards the first thin film;
 a drop port optically coupled to the first thin film and arranged to receive at least one wavelength of the multiplexed signal from the first thin film;
 an add port coupled to the second thin film and arranged to allow at least one wavelength to pass through the add port and into the second thin film; and
 an output port coupled to the optical substrate configured to receive signals from the second thin film.
9. **(Original)** The optical add/drop patch cord of claim 8, further comprising:
 an input fiber permanently coupled to the input port and optically coupled to the optical add/drop component;
 a drop fiber permanently coupled to the output port and optically coupled to the optical add/drop component;
 an add fiber permanently coupled to the add port and optically coupled to the optical add/drop component; and
 an output fiber permanently coupled to the output port and optically coupled to the optical add/drop component.

10. **(Original)** The optical add/drop patch cord of claim 8, further comprising:
 - an input fiber detachably coupled to the input port and optically coupled to the optical add/drop component;
 - a drop fiber detachably coupled to the output port and optically coupled to the optical add/drop component;
 - an add fiber detachably coupled to the add port and optically coupled to the optical add/drop component; and
 - an output fiber detachably coupled to the output port and optically coupled to the optical add/drop component.

11. **(Original)** The optical add/drop patch cord of claim 8, further wherein the input port, output port, add port and drop port each comprise a solder ferrule.

12. **(Original)** The optical add/drop patch cord of claim 8 wherein:
 - the first thin film is configured to allow at least one wavelength of an optical signal from the input fiber to pass through the first thin film towards the drop port while reflecting other wavelength(s) of the optical signal to the second thin film; and
 - the second thin film is configured to reflect the other wavelength(s) of the optical signal towards the output port while allowing at least one wavelength to pass through the thin film from the add port towards the output port.

13. **(Original)** The optical add/drop patch cord of claim 8, comprising more than four ports configured to add/drop a plurality of signals.

14. **(Original)** A method for manufacturing an optical add/drop patch cord comprising:
enclosing an optical add/drop component in a casing, the optical add/drop component comprising:
 an optical substrate;
 a first thin film formed on one end of the substrate; and
 a second thin film formed on an end opposing the one end such that the second
 thin film is opposed to the first thin film;
 optically coupling an input port to the optical substrate whereby a signal input at the input
 port will travel towards the first thin film;
 optically coupling a drop port to the optical substrate at the first thin film whereby a
 signal passing through the first thin film will propagate through the drop port and a signal
 reflected by the first thin film will be reflected towards the second thin film;
 optically coupling an add port to the optical substrate at the second thin film whereby the
 second thin film is configured to reflect the signals reflected by the first thin film towards an
 output port and to permit a signal received by the add port to pass through the second thin film
 towards the output port; and
 optically coupling the output port to the optical substrate.
15. **(Original)** The method of claim 14, further comprising soldering a fiber to at least
one of the input port, the drop port, the add port, and the output port.
16. **(Original)** The method of claim 14, further comprising constructing the add/drop
module wherein constructing comprises:
 arranging two thin film cubes having thin film substrates such that the thin films are
 diagonally opposed to each other; and
 pressing the two thin film cubes together to cause the two thin film cubes to fuse.
17. **(Original)** The method of claim 16, further comprising polishing attachment faces
on the thin film cubes where the two thin film cubes will be fused to remove irregularities and impurities.
18. **(Original)** The method of claim 14, comprising forming at least one of the first thin
film and the second thin film on the optical substrate forming comprising vapor deposition.

19. **(Original)** The method of claim 14, comprising forming at least one of the first thin film and the second thin film on the optical substrate forming comprising a film growth process.

20. **(Original)** The method of claim 14, further comprising detachably attaching optical fibers to at least one of the input fiber, the drop fiber, the add fiber, and the drop fiber.

21. **(Original)** The method of claim 14, further comprising permanently attaching optical fibers to at least one of the input fiber, the drop fiber, the add fiber, and the drop fiber.

22. **(Withdrawn)**

23. **(Withdrawn)**